



Technisches Datenblatt

Produkt / Typ	LiBa®Safe XLs <i>Innenverpackung für Lithiumbatterien</i>
Innenmaße L x B x H in mm (ca.)	1680 x 1055 x 455 mm
Außenmaße L x B x H in mm (ca.)	1825 x 1250 x 560 mm
Nettogewicht in kg (ca.)	198 kg
Bauart	Stahl-Wanne & -Deckel mit mehrlagigem Sonder-Textil / LiBa®Vent System
Hersteller	GelKoh GmbH
Löschanlage	inkl. LiBa®Sol
Auslösung	Selbstausslösend bei ca. 180 °C
Besonderheiten	LiBa®Vent System - Gasdurchlässig mit Partikelbarriere, HF-Absorbierend, Innenbeschichtung nach DIN 4102-I / A, nicht brennbar
Sonstiges	Tragegurte, Sonderverschlüsse, Staplerprofile
Einsatzbereich	Innenverpackung gem. ADR, Quarantäne-Zone / Lagerort Bei Außenlagerung unbedingt vor Wittereeinflüssen schützen, abdecken, unterstellen, etc. oder Regenhaube als Zubehör mit bestellen!
Gasmanagement	gem. ADR, HF- reduzierend

Der Hersteller bescheinigt hiermit die Eigenüberwachung des Erzeugnisses, sowie das durch die BAM anerkannte QS System. Die Herstellung erfolgte zeichnungs- und normgerecht. (Je nach Ausführung Abbildung ähnlich / Änderungen vorbehalten!)



Spec Sheet

Product / Variant	LiBa®Safe XLs <i>Inner packaging for lithium batteries</i>
Inner dimensions L x W x H (approx.)	1680 x 1055 x 455 mm
Outer dimensions L x W x H (approx.)	1825 x 1250 x 560 mm
Net weight in kg (approx.)	198 kg
Construction	Steel tray and cover with compound textile LiBa®Vent gas management system
Manufacturer	GelKoh GmbH
Extinguishing system	LiBa®Sol
Release	Self activates at ca. 180 °C
Features	LiBa®Vent system - gas permeable with particle barrier, HF-absorbing, internal coating according to DIN 4102-1 / A, non-flammable
Additional features	Lifting belts, special closures with corresponding protective strips, suitable for fork lift
Field of application	Inner packaging according to ADR quarantine zone / storage area <i>For outdoor storage: protect, cover, place underneath canopy etc., or order a rain cover as an accessory!</i>
Gas management	In accordance with ADR, HF-absorbing

The manufacturer hereby certifies the self-monitoring of the product as well as the QA system recognized by BAM.

The production was carried out in accordance with the drawings and standards.

(Depending on the version, the illustration is similar / subject to change without notice!)